

M O D E L **8700**



Engineered to be maintenance free for easy-care living, Model 8700 won't rust, fade, crack or dent.

Durable door construction


DOOR FEATURES

Foamed-in-place polyurethane insulation

with an R-value of 11.75* is permanently bonded to the vinyl skin for thermal efficiency, durability and added rigidity.

Twin 20-gauge steel C-channels

run full length of each panel and are anchored to interior steel stiles for strength.



torsion spring.

salt air and sand.

Wind Load Options wind SAFE IMPACT

Available with structural reinforcements for use in coastal or high wind region.

TorqueMaster® Plus Counter Balance System

• 15 Year Limited Warranty

High Cycle Spring Option



PVC color construction means scratches are less visible because the color goes all the way through the material. The UV-Resin used in the door's

sun's harmful ultraviolet rays. Ideal for coastal regions for its resistance to

Contains springs safely inside a steel tube to prevent accidental release of


tension that could cause injury and features anti-drop safety technology.


Choose a 25,000 cycle spring for more than twice the life of a standard

construction contains special polymers that protect the door from the

^{*}Wayne Dalton uses a calculated door section R-value for our insulated doors.

Choose Your Style





Choose Your Color





Glacier White

Adobe Cream





Monterey Sand

Cape Cod Gray

Actual door colors may vary slightly from the brochure due to fluctuations the printing process. Always request a color sample from your Wayne Dalton Dealer for accurate color matching.

Choose Your Windows

Designer Windows





Cathedral I







Williamsburg I

Optional insulated glass available for improved thermal performance. Designer windows are available with clear glass only.

Etched Windows

Privacy glass







Diamond

Eclipse

Prairie

Clear glass







Diamond

Eclipse

Prairie





2501 S. State Hwy 121 Bus., Ste 200 Lewisville, TX 75067

wayne-dalton.com









